

Cerberus produkt line

Produkt specification Cerberus printer TA-451



Specifications:

TEMPEST compliance SDIP 27 Level A (BSI⁽¹⁾ certified configuration)

Service 12 months bring-in repair service included; 36 months optional

Specifications printer ⁽²⁾

Print Speed	Up to 21 ppm letter
Document delivery speed	First Page out as fast as 17 seconds color (letter, ready)
Print Resolution	Up to 600 x 600 dpi
Print technologie	Laser
Duty cycle (monthly, letter)	Up to 40.000 pages
Recommended monthly page volume	Up to 750 to 2.000 pages
Memory	128 MB
Standard print languages	HP PCL 5c, HP PCL 6, HP Postscript level 3 emulation

⁽¹⁾ Bundesamt für Sicherheit in der Informationstechnik (Federal Office for Information Security)

⁽²⁾ According to the manufacturer's data of Hewlett Packard®

Specifications printer ⁽¹⁾ (continuation)

Interface optional:	LWL 100Base-FX ST, Adapter optional; TEMPEST D-Sub 9 polig Hi-Speed USB 2.0
Product Dimensions (w/d/h)	405 x 484 x 322 mm
Weight	23,6 kg
Client operating system	Windows 8; Windows 7 (32/64 Bit); Windows Vista (32/64 Bit); Windows Server 2008 (32/64 Bit); Windows Server 2003 (32 Bit) (SP3 or higher); Mac OS X v10.5, v10.6; Linux; Unix
Power consumption (Aktive)	425 watts
Power consumption (Sleep)	4 watts
Power consumption (Ready)	15,2 watts
Power consumption (Off)	0,5 watts
Recommended temperature	15 to 30 degrees F
ENERGY STAR®-certified	yes
Acoustic	Accoustic Pressure Emission Bystander: 51 dB(A)

Paper⁽¹⁾

Paper trays	2
Paperhandling	Input Capacity: up to 300 sheets, up to 10 envelopes Output Capacity: up to 150 sheets, up to 20 envelopes
Duplex print option	Automatic
Media Sizes supported	Tray 1/Tray 2: Letter, legal, executive, 8.5x13 in, 3x5 in, 4x6 in, 5x8 in, envelopes (No 10, Monarch)
Media Types supported	Paper (bonded, brochure, colored, glossy, photo, plain, preprinted, prepunchad, recycled, rough), postcards, transparencies, labels, envelopes

⁽¹⁾ According to manufacturer's data of Hewlett Packard®