

# CERBERUS product line

## Product specification CERBERUS printer TA-2035



### Specifications

TEMPEST compliance	SDIP 27 Level A (BSI <sup>(1)</sup> certified configuration)
Service	12 months bring-in repair service included; 36 months optional

### Technical Data<sup>(2)</sup>

Print speed (black, A4)	Up to 30 ppm
First page out (black)	As fast as 8 sec (from "ready")
Print resolution	Up to 600 x 600 dpi
Print technology	Laser
Duty cycle (monthly, A4)	Up to 25,000 pages
Recommended monthly page volume	500 to 2,500 pages
Memory	16 MB (not expandable)
Processor speed	266 MHz
Printer languages	Host Based, UPD (HP PCL5e)

<sup>(1)</sup>Bundesamt für Sicherheit in der Informationstechnik (Federal Office for Information Security)

<sup>(2)</sup>According to manufacturer's data of Hewlett Packard®

## Technical Data<sup>(1)</sup> (continuation)

Connections	USB 2.0, IEEE 1284-compliant parallel
Product dimensions	365 x 368 x 268 mm
Weight	app. 10 kg (22.05 lbs)
Compatible operating systems	Windows 7 ready (some features may not be available), Windows Vista (32/64 Bit), Windows XP (32/64 Bit), Windows Server 2003 (32/64 Bit), Windows 2000, NT 4.0, MAC OS X v10.3.9, v10.4.3, v10.5, v10.6, UNIX, Linux
Power consumption (active)	550 watts
Power consumption (sleep)	7 watts
Power consumption (ready)	7 watts
Power consumption (off)	0,4 watts
Recommended temperature	17.5 to 25° C (63.5 to 77° F)

## Paper Handling<sup>(1)</sup>

Paper trays	2
Input capacities	Tray 1: 50 sheets, 5 envelopes, 75 transparencies Tray 2: 250 sheets
Output capacities	Up to: 150 sheets, 5 envelopes, 75 transparencies; 150-sheet output bin
Duplex printing	Manual (driver support provided)
Media sizes	Tray 1: A4, A5, A6, B5, envelopes (C5, B5, DL); 76 x 127 to 216 x 356 mm Tray 2: A4, A5, A6; 105 x 148 to 216 x 356 mm
Media types supported	Paper (bond, light, heavy, plain, recycled, rough), envelopes, labels, cardstock, transparencies, heavy media

<sup>(1)</sup>According to manufacturer's data of Hewlett Packard®