

CERBERUS product line

Product specification CERBERUS printer TA-M855



Specifications

TEMPEST compliance	SDIP 27 Level A (BSI ⁽¹⁾ certified configuration)
Service	12 months bring-in repair service included; 36 months optional

Technical Data⁽²⁾

Print speed	Up to 46 ppm
First page out	As fast as 11 sec
Print resolution	Up to 1200 x 1200 dpi
Print technology	Laser
Duty cycle (monthly, A4)	Up to 175,000 pages
Recommended monthly page volume	4,000 to 25,000 pages
Memory	1.5 GB
Processor speed	800 MHz
Printer languages	HP PCL6, HP PCL5, HP postscript level 3 emulation

⁽¹⁾Bundesamt für Sicherheit in der Informationstechnik (Federal Office for Information Security)

⁽²⁾According to manufacturer's data of Hewlett Packard®

Technical Data⁽¹⁾ (continuation)

Connections	F/O 1000 SC, USB 2.0
Product dimensions	1000 x 635 x 580 mm
Weight	86 kg (189.6 lbs)
Compatible operating systems	Windows 7, Windows 8, Windows 10, Windows Vista, Windows XP, Windows Server 2003, MAC, Linux
Power consumption (active)	1100 watts
Power consumption (sleep)	7 watts
Power consumption (ready)	60 watts
Power consumption (off)	0,4 watts
Recommended temperature	15 to 30° C (59 to 86° F)
ENERGY STAR®-certified	Yes

Paper Handling⁽¹⁾

Paper trays	2
Input capacities	100-sheet multipurpose tray, 500-sheet input tray
Output capacities	500-sheet face-down bin
Duplex options	Automatic
Media types supported	Cut sheet paper, labels, transparencies, glossy paper, glossy film, photo media, tough paper, envelopes
Media sizes custom	Tray 1: 3 x 5 to 12.6 x 18 in Tray 2: 5.8 x 8.3 to 11.7 x 17 in
Media sizes supported	Tray 1: letter, letter-r, legal, executive, ledger (11 x 17), 8.5 x 13, 12 x 18, statement, index card (4 x 6, 5 x 7, 5 x 8, 3 x 5), envelopes: #9, #10, monarch Tray 2: letter, letter-r, legal, executive, ledger (11 x 17), 8.5 x 13
Media weight supported	Tray 1, 2: 16 to 58 lbs

⁽²⁾According to manufacturer's data of Hewlett Packard®